




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837 **EnerSys EMEA** EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland PDF Generated 12/19/2023 Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet

ODP-AGM34R

(34R-790)

Battery Type



- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	1500A
Cold Cranking Amps (CCA)	800A
НСА	1200A
MCA	1000A
20Hr Nominal Capacity (Ah)	65Ah
10Hr Nominal Capacity (Ah)	57Ah
Reserve Capacity Minutes	130 mins
Terminal	SAE
Torque Spec in-lbs (Nm max)	N/A
Internal Resistance (m Ω)	2.9 mΩ
Short Circuit (A)	2400A
UPC	635241140583

Dimensions and Weight

Length	10.8 in / 274 mm
Width	6.8 in / 173 mm
Height (terminals included)	7.9 in / 201 mm
Height (container)	7.4 in / 188 mm
Weight	46.6 lbs / 21.1 kg

Temperature

Operating temperature range	-40°F/-40°C to 140°F/+60°C
Optimum storage temperature	68°F/+20°C

Accreditations

EnerSys Asia

Building

152 Beach Road

Singapore 189721 Tel: +65 6416 4800

#11-08 Gateway East

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016

Want more info? Scan code to access the ODYSSEY® Battery Literature Library



G batteries

© 2023 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted. Subject to revisions without prior notice. E.&O.E. Date Downloaded: December 19, 2023

www.odysseybattery.com www.enersys.com

