





# Drawings & Terminal Position



ODP-AGM94R/H7/L4 RIGHT POSITIVE SAE TERMINALS



### **Handling and Storage**

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

## **Charging and Self-Discharge**

Type of charging curve IUU

Charger voltage at 68°F (20°C) 14.4V to 14.8V

Self-discharge per month at 68°F (20°C) 1.25%

Self-discharge per month at 104°F (40°C) 5%

80% depth of discharge cycles 400



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837 EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland

# EnerSys Asia 152 Beach Road #11-08 Gateway East and Building Singapore 189721

Tel: +65 6416 4800

PDF Generated 12/19/2023 Information correct at time of exporting PDF. Please check website for updates.

#### **Technical Data Sheet**

#### **ODP-AGM94R H7 L4**

(94R-850 (LN4-H7))



#### **Battery Type**

- With SAE posts
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

#### **Power and Performance**

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	1500A
Cold Cranking Amps (CCA)	850A
HCA	1200A
MCA	1000A
20Hr Nominal Capacity (Ah)	80Ah
10Hr Nominal Capacity (Ah)	76Ah
Reserve Capacity Minutes	155 mins
Terminal	SAE
Torque Spec in-lbs (Nm max)	N/A
Internal Resistance (m $\Omega$ )	$5.7~\text{m}\Omega$
Short Circuit (A)	2250A
UPC	635241140620

#### **Dimensions and Weight**

Length	12.4 in / 315 mm
Width	6.9 in / 175 mm
Height (terminals included)	7.4 in / 188 mm
Height (container)	7.5 in / 191 mm
Weight	54.8 lbs / 24.9 kg

#### **Temperature**

Operating temperature range  $-40^{\circ}\text{F}/-40^{\circ}\text{C}$  to  $140^{\circ}\text{F}/+60^{\circ}\text{C}$ Optimum storage temperature  $68^{\circ}\text{F}/+20^{\circ}\text{C}$ 

#### **Accreditations**

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

\*Cold Start Performance S.A.E J537 Apr 2016

Want more info? Scan code to access the ODYSSEY® Battery Literature Library



