




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837 **EnerSys EMEA** EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland PDF Generated 12/14/2023 Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet

ODS-AGM16LMJ

(PC680MJ)

Battery Type



- Group 16 Absorbed Glass Mat (AGM) battery with Thin Plate Pure Lead (TPPL) and metal jacket
- Up to 400 cycles at 80% depth of discharge
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	520A
Cold Cranking Amps (CCA)	170A
НСА	350A
MCA	280A
20Hr Nominal Capacity (Ah)	16Ah
10Hr Nominal Capacity (Ah)	16Ah
Reserve Capacity Minutes	24 mins
Terminal	M6 Receptacle
Torque Spec in-lbs (Nm max)	50 (5.6)
Internal Resistance (m Ω)	7 mΩ
Short Circuit (A)	1800A
UPC	635241141009

Dimensions and Weight

Length	7.3 in / 185 mm
Width	3.1 in / 79 mm
Height (terminals included)	6.4 in / 163 mm
Height (container)	6.7 in / 170 mm
Weight	16.6 lbs / 7.5 kg

Temperature

Operating temperature range	-40°F/-40°C to 176°F/+80°C
Optimum storage temperature	68°F/+20°C

Accreditations

EnerSys Asia

Building

152 Beach Road

Singapore 189721 Tel: +65 6416 4800

#11-08 Gateway East

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016

Want more info? Scan code to access the ODYSSEY® Battery Literature Library





© 2023 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted. Subject to revisions without prior notice. E.&O.E. Date Downloaded: December 14, 2023

www.odysseybattery.com www.enersys.com