



Drawings & Terminal Position

Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

| Type of charging curve | IUU |
|--|----------------|
| Charger voltage at 68°F (20°C) | 14.4V to 14.8V |
| Self-discharge per month at 68°F (20°C) | 1.25% |
| Self-discharge per month at 104°F (40°C) | 5% |
| 80% depth of discharge cycles | 400 |

PDF Generated 12/14/2023 Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet

ODS-AGM470FTT

(PC1800-FT)

Battery Type



- 3/8 inch threaded front stud terminal
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

| Voltage | 12V |
|--|----------------------|
| Pulse (5 second) Hot Cranking Amps (PHCA) | 1800A |
| Cold Cranking Amps (CCA) | 1300A |
| HCA | 1600A |
| MCA | 1450A |
| 20Hr Nominal Capacity (Ah) | 214Ah |
| 10Hr Nominal Capacity (Ah) | 190Ah |
| Reserve Capacity Minutes | 475 mins |
| Terminal | 3/8-16" Stud |
| Torque Spec in-lbs (Nm max) | 80 (9.0) |
| Internal Resistance (m Ω) | $3.3~\text{m}\Omega$ |
| Short Circuit (A) | 3800A |
| UPC | 635241140859 |

Dimensions and Weight

| Length | 22.9 in / 582 mm |
|-----------------------------|-------------------|
| Width | 4.9 in / 124 mm |
| Height (terminals included) | 12.5 in / 318 mm |
| Height (container) | 12.5 in / 318 mm |
| Weight | 132 lbs / 59.9 kg |

Temperature

Operating temperature range $-40^{\circ}\text{F}/-40^{\circ}\text{C}$ to $113^{\circ}\text{F}/+45^{\circ}\text{C}$ Optimum storage temperature $68^{\circ}\text{F}/+20^{\circ}\text{C}$

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016

Want more info? Scan code to access the ODYSSEY® Battery Literature Library





EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837 EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland EnerSys Asia 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800

