




# **Drawings & Terminal Position**



# Handling and Storage

- Can be mounted or stored in any orientation except
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

# **Charging and Self-Discharge**

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400



EnerSys World Headquarters

2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland **EnerSys Asia** 152 Beach Road #11-08 Gateway East

Building Singapore 189721 Tel: +65 6416 4800

PDF Generated 12/15/2023 Information correct at time of exporting PDF. Please check website for updates.

## **Technical Data Sheet**

## ODX-AGM31A

(31-PC2150T)



## **Battery Type**

- Group 31 with brass SAE automotive posts and single external vent
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep

#### **Power and Performance**

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	2150A
Cold Cranking Amps (CCA)	1150A
HCA	1545A
MCA	1370A
20Hr Nominal Capacity (Ah)	103Ah
10Hr Nominal Capacity (Ah)	98Ah
Reserve Capacity Minutes	220 mins
Terminal	SAE
Torque Spec in-lbs (Nm max)	N/A
Internal Resistance (m $\Omega$ )	$2.2~\text{m}\Omega$
Short Circuit (A)	5000A
UPC.	635241140460

# **Dimensions and Weight**

Length	13 in / 330 mm
Width	6.8 in / 173 mm
Height (terminals included)	9.7 in / 246 mm
Height (container)	8.5 in / 216 mm
Weight	77.8 lbs / 35.3 kg

### **Temperature**

Operating temperature range -40°F/-40°C to 176°F/+80°C Optimum storage temperature 68°F/+20°C

### Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

\*Cold Start Performance S.A.E J537 Apr 2016

Want more info? Scan code to access the ODYSSEY® Battery **Literature Library** 



