





RB48V200

Voltage: 51.2V | Capacity: 200 Ah | Energy: 10.24 kWh

LITHIUM IRON PHOSPHATE BATTERY LifePO4

ELECTRICAL SPECIFICATIONS		
Nominal Voltage	51.2 V	
Nominal Capacity	200 Ah	
Capacity @ 25A	480 min	
Resistance	≤10 mΩ @ 50% SOC	
Efficiency	99%	
Self Discharge	<3% per Month	
Maximum Modules in Series	1 (Single Use)	

DISCHARGE SPECIFICATIONS	
Maximum Continuous Discharge Current	200 A
Peak Discharge Current	250 A (4 s ±1 s)
BMS Discharge Current Cut-Off	390 A (5 s)
Recommended Low Voltage Disconnect	44 V
BMS Discharge Voltage Cut-Off	40 V (2.5 ±0.1 vpc)
Reconnect Voltage	40.5 V (2.53 ±0.1 vpc)
BMS SOC Disconnect	5%


TEMPERATURE SPECIFICATIONS		
Discharge Temperature	-4 to 131 °F (-20 to 55 °C)	
Charge Temperature*	-4 to 131 °F (-20 to 55 °C)	
Storage Temperature	23 to 95 °F (-5 to 35 °C)	
BMS High Temperature Cut-Off	149 °F (65 °C)	
Reconnect Temperature	145 °F (63 °C)	
BMS Low Temperature Disconnect	-4 °F (-20 °C)	
Reconnect Temperature	-0.4 °F (-18 °C)	

^{*}Refer to charge currents below 32°F (0°C)

MECHANICAL SPECIFICATIONS	
Dimensions (L x W x H)	34.3 x 14.2 x 15.6" 872 x 361 x 395 mm
Weight	302 lbs (137 kg)
Terminal Type	M10 x 1.5
Terminal Torque	110 - 125 in-lbs (12.2 - 14 N-m)
Case Material	Steel Case
Enclosure Protection	IP65
Cell Type - Chemistry	Cylindrical - LiFePO ₄

CHARGE SPECIFICATIONS	
Recommended Charge Current	≤100 A
Recommended Maximum Charge Current	200 A
BMS Charge Current Disconnect	300 A
Charge Current 14 to 32 °F (-10 to 0 °C)	≤0.1 C
Charge Current -4 to 14 °F (-20 to -10 °C)	≤0.05 C
Recommended Charge Voltage	56.0 V - 58.4 V
BMS Charge Voltage Disconnect	60.8 V (3.9 vpc)
Reconnect Voltage	60.3 V (3.87 vpc)

COMPLIANCE SPECIFICATIONS	
Certifications	UN38.3 & CE (battery) UL1642 (cells) (File# MH64523) IEC62133 (cells)
Shipping Classification	UN 3480, CLASS 9











RB48V200

Voltage: 51.2V | Capacity: 200 Ah | Energy: 10.24 kWh

LITHIUM IRON PHOSPHATE BATTERY LIFEPO4

